


# kreon project downlight 2"




# kreon project downlight 2"



project downlight 2" directional,  
white, with trim



project downlight 2" downlight,  
black, trimless



project downlight 2" directional,  
bronze, trimless



colour temperature

<b>CCT options</b>	2400K, 2700K, 3000K, 3500K, 4000K
<b>dim-to-warm</b>	1800K - 2700K
<b>tunable white</b>	2700K - 5000K



CRI

**CRI 97**  
high CRI LED engines  
for accurate colour rendering



lumen output  
**> 1000 lm**



UGR

**UGR ≤ 12**

low glare optics with refined cut-off



beam angle



efficiency

**> 100 lm/W**

narrow spot	12°
spot	18°
narrow flood	26°
medium flood	38°
wide flood	51°



colour

painting


brushed plated



kreon up 40 linear



# kreon up 40 linear



up 40 linear diffuse & wallgrazer



up 40 linear diffuse, double



up 40 linear wallgrazer, double



colour temperature

2700K



CRI

CRI90+



IP

IP67



lumen output @ 2700K

diffuse 140 lm

wallgrazer 633 lm



function

diffuse uplight  
wallgrazer



application

recessed in-ground  
surface wall



colour

black



kreon vergo



# kreon vergo



vergo directional



vergo cone 1



vergo cone 2



colour temperature

**directional** 2700K, 3000K  
**cone** 2700K



CRI

**CRI90**



ingress protection

**IP67**



lumen output @ 2700K

**directional** 361 lm  
**cone** 350 lm



function

**outdoor**  
**24V plug&play system**  
**directional**  
**ambient downlight**



beam angle

**dark light** 20°  
**wide dark light** 38°  
**diffuse**



colour

**black**



(other RAL-colours on request)

# kreon bar



kreon bar, brushed bronze



kreon bar, ceramic cream white



lumen output

**CCT options**  
2200K, 2700K



efficiency

**ERP F**



colour

painting

brushed plated



lumen output

up to 200 lm



battery

**rechargeable**

up to 9 hours of power (at 100%)  
after a full charge



dimming

**touch-dim**

